

# Conversol V5 Super Off-Grid Inverter



- Zero transfer time to protect mission-critical loads such as servers and ATM.
- Detachable LCD control module with multiple communications
- Built-in Bluetooth for mobile monitoring (Android App is available)
- Supports USB On-the-Go function
- Reserved communication port for BMS (RS48S, CAN-BUS or RS232)
- Configurable AC/PV output usage timer and prioritization
- Optional parallel operation up to 9 units

## Axpert King Off-Grid Inverter Selection Guide

MODEL	Axpert King 3K	Axpert King 5K
Rated Power	3000VA/3000W	5000VA/5000W
Parallel Capability	Up to 9 units	Up to 9 units
<b>INPUT</b>		
Voltage	230 VAC	
Voltage Range	110-280 VAC	
Frequency Range	50 Hz/60 Hz (Auto sensing)	
<b>OUTPUT</b>		
AC Voltage Regulation	230VAC $\pm$ 5%	
Output THDv	<3% for linear load, <8% for non-linear load	
Surge Power	6000VA for 5 sec	10000VA for 5 sec
Efficiency (Peak)	93 % at Line Mode, 90% at Battery Mode	
Transfer Time	0ms	
Waveform	Pure sine wave	
<b>BATTERY</b>		
Battery Voltage	24 VDC	48VDC
Floating Charge Voltage	27VDC	54 VDC
Overcharge Protection	34 VDC	66VDC
<b>SOLAR CHARGER &amp; AC CHARGER</b>		
Solar Charger Type	MPPT	MPPT
Maximum PV Array Open Circuit Voltage	145 VDC	
Maximum PV Array Power	1500W	4000W
MPP Range@ Operating Voltage	30 ~ 115 VDC	60~115VDC
Maximum Solar Charge Current	60A	80A
Maximum AC Charge Current	60A	60A
Maximum Charge Current	120A	140A
<b>PHYSICAL</b>		
Dimension, D x W x H (mm)	140 X 303 X 525	
Net Weight (kgs)	13.0	13.5
Communication Interface	USB/RS232/RS485/Bluetooth/Dry-contact	
<b>ENVIRONMENT</b>		
Humidity	5% to 95% Relative Humidity (Non-condensing)	
Operating Temperature	0 <sup>o</sup> c to 55 <sup>o</sup> c	
Storage Temperature	-15 <sup>o</sup> C to 60 <sup>o</sup> C	

Product specifications are subject to change without further notice.